


## CP TEST STATION MODEL T-3

The Model T-3 is the most versatile Cathodic Protection Test Station available. UV stabilized, Fire resistant and Impact resistant poly carbonate material for long outdoor life.

Fits 3.5" OD riser pipe, also available from stock in three colors. Reducing adapters available for smaller O.D.'s, and a flange adapter, as well.

Large, clear terminal board can handle a variety of custom configurations, including voltmeters, shunts, resistors, potentiometers and more.

See our website for more information



WWW.

teststations.

.com

Distributed by

Features:

8 Colors

11 terminal positions

5 Rapid Connect binding posts

Clear terminal board

UV Stabilized color

Fire resistant, impact resistant

Fits 3.5" OD Risers (also available)

Shunts and other accessories available



**AVAILABLE FROM STOCK!**

[www.teststations.com](http://www.teststations.com)


[www.detectron.com](http://www.detectron.com)

[www.tinker-rasor.com](http://www.tinker-rasor.com)

[Info@tinker-rasor.com](mailto:Info@tinker-rasor.com)



Tinker & Rasor quality is found in our products,  
our people and our customer service.





# TINKER & RASOR

CORROSION MITIGATION INSTRUMENTATION

## PRODUCT DATA SHEET MODEL T-3 CP TEST STATIONS

### Features:

- 11 hole terminal board
- 5 Rapid connection binding posts
- Clear terminal board
- 8 colors from stock
- Fits 3.5" OD riser pipe
- UV Stabilized color protection
- High impact resistance
- Fire resistant
- "Easy Grip" top for easy opening with gloves
- "Anti-Spin" gasket prevents twisting

### Construction:

Polycarbonate material (Lexan®) gives great UV stabilization, fire protection and impact resistance. Rapid connection binding posts are nickel plated brass for excellent corrosion resistance.

### Applications:

- Cathodic Protection connection point

### Recommendations:

Use with optional items such as the T&R Shock Guard which can be combined with banana jacks for personnel safety. Also can be custom printing which may meet DOT ID requirements for urban environments.

### Environment:

-76°C to 122°C (-105°F to 252°F)

### Dimensions:

Complete Test Station:  
Terminal Board: 5.3" x 3.52" (134.6mm x 89.4mm)  
Cover: 5.1" x 4.4" (129.5mm x 111.75mm)  
Shipping -  
Weight: 1 lbs (0.45 kg)  
Dimensions: 6" x 6" x 4"  
(152mm x 152mm x 101.6mm)

DELIVERY: **Immediately from STOCK**  
F.O.B. San Bernardino, CA USA  
SERVICE: **24-hour Turn-Around**  
TERMS: Net30 Days, on approval of credit  
WARRANTY: **90 Days**, parts and labor



Model T-3 CP Test Stations come standard with the unique Tinker & Rasor binding post with set screw. This binding post allows for rapid wire connections on wires as big as 6 AWG. Each T-3 comes with five (5) nickel plated binding posts, and up to eleven (11) binding posts on custom orders.

The T-3 also features a clear terminal board made of a tough, fire resistance polycarbonate resin. The clear terminal allows you to view both sides of the terminal board without obstruction.

The terminal board has eleven (11) terminal positions, most on 1" centers from another, and can be filled with our binding posts, stainless screws or banana jacks, on custom orders.



Custom configurations and printing available on Model T-3 test stations



[www.teststations.com](http://www.teststations.com)

**AVAILABLE FROM STOCK**