


RADIO LOCATOR PROBE



MODEL TS-8 HANDHELD PROBE FOR USE WITH 505 GO-FER LOCATOR

Hand held probe for use with Model 505 Receiver.

The addition of the TS/8 Probe to the Model 505 Pipe & Cable Locator kit gives the operator a search coil much closer to the ground, saving the back strain of bending over on difficult locates.

The TS/8 also makes depth determination much easier!



Distributed by

Easy to operate
Unaffected by
surface cover
Light weight
Telescoping handle
Rugged Construction
Water resistant

AVAILABLE FROM STOCK!

www.teststations.com

www.detectron.com



www.tinker-rasor.com

Info@tinker-rasor.com

An ISO 9001 Registered Company

Tinker & Rasor quality is found in our products, our people and our customer service.



DETECTRON LOCATORS



TINKER & RASOR

CORROSION MITIGATION INSTRUMENTATION

PRODUCT DATA SHEET

MODEL TS/8 HANDHELD PROBE

Features:

- Easy to operate
- Unaffected by surface cover
- Light weight and strong
- Water resistant
- Telescoping handle
- Depth locator "bubble"

Construction:

Rugged construction, made of anodized aluminum and strong resin plastic. Probe is sealed and weather resistant. Comfortable neoprene handle.

Applications:

- Pipe & Cable locating
- Short locating
- Pipe depth determination

Recommendations:

- Use to relieve frequent bending or kneeling during locates and depth determination

Specifications:

Use with Model PD and Model Mark V Ranger
Designed to receive signal from either locator transmitter

Dimensions:


Length: 34" (863.5mm)
Operating Weight: 1.5 lbs (0.68kg)
Shipping Weight: 3 lbs. (1.36kg)
Shipping Dimensions:
4" x 4" x 32"
(101.6mm x 101.6mm x 812.8mm)

DELIVERY: **Immediately from STOCK**
F.O.B. San Gabriel, CA USA

SERVICE: **24-hour Turn-Around**

TERMS: Net30 Days, on approval of credit

WARRANTY: **90 Days**, parts and labor




Model 505
Receiver

Use the TS-8 Probe with the **Model 505 "Go-fer" Pipe & Cable Locator**

Works with the **Tinker & Rasor Model Mark V Ranger** Transmitter also! (for Radio frequency applications)

The Model TS/8 is very easy to use.
The single plug-in cable connector is located at the top of the handle.
The 45° bubble on the handle makes depth locating a breeze.



MODEL TS/8 Connection and Bubble

AVAILABLE FROM STOCK