



CORROSION MITIGATION INSTRUMENTATION
2828 FM 758, NEW BRAUNFELS, TX 78130 TEL: (830) 253-5621

PRODUCT INSTRUCTIONS

T-1 INSTRUCTIONS

Prior to installation check parts list!

- Step 1.** Install connecting hardware, binding post or other accessories into the holes in the T-1 test station terminal. Most Model T-1 CP Test Stations will come with three (3) binding posts installed.
- Step 2.** Install Tinker & Rasor's exclusive "anti-spin" gasket. Remove protective paper from one side of gasket and place sticky side inside the terminal and press firmly. Remove the remaining protective paper cover from the gasket.
- Step 3.** Place black nut over 1-1/2" OD test station riser. (custom color nuts available)
- Step 4.** Thread the cables through bottom of the T-1 terminal.
- Step 5.** Position the T-1 terminal to the desired alignment over the riser and press down firmly. The "anti-spin" gasket will seal the terminal to the riser. Tighten terminal to riser pipe with the large black nut while holding the terminal.
- Step 6.** Attach cables as required.

To unlock the Top: Twist the Top counter-clockwise to remove.

For Questions or comments contact:

Tinker & Rasor
2828 FM 758
New Braunfels, TX 78130
Phone: (830) 253-5621
E-mail: info@tinker-rasor.com
www.teststations.com

Web: www.tinker-rasor.com

E-mail: Info@tinker-rasor.com

QMF-570 010-163