

TINKER & RASOR BE AWARE

- IMPORTANT: READ INSTRUCTION MANUAL BEFORE USE
- If operated continually over 10 Amps, circuit breaker will open.
 - This instrument will get hot if operated continually over 3 Amps.
 - The internal battery will not function when below 9 volts.
 - Continuous exposure to direct sunlight may cause display to darken.
 - Keep the inside of this instrument free of moisture.
 - If the protection fuse continues to open, allow unit to cool.
 - If unit is hot, remove center panel screw and set instrument chassis on case for air cooling.
- www.tinker-rasor.com
info@tinker-rasor.com

12V CHARGER
(INTERNAL LI BATTERY)

EXTERNAL POWER

INPUT

RANGE
External power source recommended when output exceeds 1 Amp.

10A BATT. TEST

ADJUST

9V BATTERY

LOAD LIFTING INDICATOR

INTERRUPT SECONDS
OFF - ON

INTERRUPT CYCLES

Pos	Sec. Off/On
1	CONTINUOUS
2	0.2 - 0.8
3	0.3 - 0.7
4	1 - 4
5	2 - 8
6	6 - 14

TINKER & RASOR

MODEL CS - 10

10 AMP PORTABLE CURRENT SUPPLY

www.tinker-rasor.com

CAUTION: PANEL SURFACE SUBJECT TO HIGH TEMPERATURES

MADE IN THE U.S.A.